# PRODUCT DATA SHEET HydroStrip HS-311PS



## Surface Preparation Coating and Installation Aid for Concrete and Metal Surfaces



PHYSICAL PROPERTIES OF LIQUID BUTYL PRIMER	
Description	HS-311PS
Color:	Black
% Solids:	20% minimum
Solvent Type:	VMP Naphtha
Flash Point:	76°F
Weight / Gallon:	7.6 Pounds
Dry Time @ 77°F (25°C):	15-20 minutes
Dry Time @ 40°F (4°C):	30-40 minutes
Clean Up:	Mineral Spirits
Coverage Per Gallon:	Approx. 300 s.f. on wet cast concrete
Min. Storage Temperature:	32°F
Min. Application Temperature:	0°F
Surface When Dry:	Flat black, non-tacky
Shelf Life:	2 years

## Where to use *HydroStrip* Liquid Butyl Primer

For use on concrete or metal surfaces, HS-311PS Solvent Based Surface Primer is a concrete surface preparation coating and installation aid for bonding preformed sealants. HS-311PS Solvent Based Surface Primer can be applied in advance of product installation.

### **Sealing Properties**

When applied to concrete or metal, HydroStrip HS-311PS Liquid Butyl Primer creates a butyl rubber film that acts to both seal the structure and improve the bond of preformed sealants.

#### **Limited Warranty**

This information is presented in good faith, but we cannot anticipate all conditions under which this information and our products, or the products of other manufactures in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products, either alone or in combination with other products. Users are advised to make their own tests to determine the safety and suitability of each such product or product combinations for their own purposes. It is the users' responsibility to satisfy himself as to the suitability and completeness of such information for this own particular use. We sell this product without warranty, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of this product, whether used alone or in combination with other products.

141 Hammond Street Carrollton, GA 30117

> Phone 770-832-2000 • 800-862-4835 • FAX 770-832-2095 Visit our website @ www.bometals.com Address email to info@bometals.com

Founded in 1989, BoMetals has become an industry leader in the design and manufacture of concrete and masonry accessories.