



Safety Data Sheet

Product Name: SSP-200 Component B
Revision Date: 2021/July

Solid Solution Products encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

Section 1. Identification of the substance/preparation and of the company/undertaking

1.1 Product identifiers

Product Name

SSP-200 Component B Polyol

Chemical Name: Polyol Blend

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Component(s) for the manufacture of urethane polymers. For industrial use.

1.3 Details of the supplier of the safety data sheet

COMPANY IDENTIFICATION

Solid Solution Products
3051 E La Jolla St., Suite G
Anaheim, CA 92806
United States

1.4 EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: INFOTRAC 1-800-535-5053
Local Emergency Contact: 1-714-747-5785

Section 2. Hazards Identification

2.1 Classification of the substance or mixture

Classification - REGULATION (EC) No

Acute toxicity (Inhalation)	Category 2	H332	Harmful if inhaled.
--------------------------------	------------	------	---------------------

Skin corrosion/irritation	Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation	Category 2	H319	Causes serious eye irritation.
Respiratory sensitization	Category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitization	Category 1	H317	May cause an allergic skin reaction.
Specific target organ toxicity - single exposure (Inhalation) (Respiratory tract irritant)	Category 3	H335	May cause respiratory irritation.
Carcinogenicity	Category 2	H351	Suspected of causing cancer.
Specific target organ toxicity - repeated exposure (Inhalation)	Category 2	H373	May cause damage to organs through prolonged or repeated exposure.

Classification according to EU Directives 67/548/EEC or 1999/45/EC

	<u>Carcinogen category 3.</u>	<u>R40</u>	<u>Limited evidence of a carcinogenic effect.</u>
Xn		R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation
Xn		R20	Harmful by inhalation.
Xi		R36/37/38	Irritating to eyes, respiratory system and skin.
		R42/43	May cause sensitization by inhalation and skin contact.

Additional Information

Contains aromatic hydrocarbons. See information supplied by the manufacturer.

2.2 Label elements

Labelling - REGULATION

Hazard pictograms



Signal Word: Danger

Hazard statements:

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements:

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P285 In case of inadequate ventilation wear respiratory protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P309 + P311 IF exposed or if you feel unwell: Call a POISON CENTER or doctor/ physician.

2.3 Other Hazards

No information available.

Section 3. Composition/information on ingredients

3.1 Substance

This product is a substance. The composition of this formula is a trade secret

CAS-No.	Amount	Component	Classification: REGULATION (EC) No 1272/2008
25791-96-2	Trade Secret	Polyether Polyol	Eye cor/irr, 2, H319 Skin Sens., 1, H317
102-60-3	Trade	Polyether Polyol	Eye cor/irr, 2, H319
64742-94-5	15.0 – 35.0 %	Aromatic Solvent Naptha Petroleum	Carc. 3: R40; Xn: R20, R48/20; Xi: R36/37/38; R42/43

For the full text of the H-Statements mentioned in this Section, see Section 16.

See Section 16 for full text of R-phrases.

Note: CAS 101-68-8 is an MDI isomer that is part of CAS 9016-87-9.

Section 4. First-aid measures

4.1 Description of first aid measures

General advice: First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Skin Contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands. Suitable emergency safety shower facility should be available in work area.

Eye Contact: Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

4.2 Most important symptoms and effects, both acute and delayed

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

4.3 Indication of immediate medical attention and special treatment needed

Maintain adequate ventilation and oxygenation of the patient. May cause respiratory sensitization or asthma-like symptoms. Bronchodilators, expectorants and antitussives may be of help. Treat bronchospasm with inhaled beta2 agonist and oral or parenteral corticosteroids. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

Section 5. Fire Fighting Measures

5.1 Extinguishing Media

Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Extinguishing Media to Avoid: Do not use direct water stream. May spread fire.

5.2 Special hazards arising from the substance or mixture

Hazardous Combustion Products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Nitrogen oxides. SO₂. SO₃. Carbon monoxide. Carbon dioxide.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Dense smoke is produced when product burns.

5.3 Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Stay upwind. Keep out of low areas where gases (fumes) can accumulate. Water is recommended, but may be applied in large quantities as a fine spray when other extinguishing agents are not available. Do not use direct water stream. May spread fire. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container.

Move container from fire area if this is possible without hazard. Use water spray to cool fire-exposed containers and fire-affected zone until fire is out. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

Special Protective Equipment for Firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

Section 6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures: Isolate area. Keep unnecessary and unprotected personnel from entering the area. Keep personnel out of low areas. Keep upwind of spill. Spilled material may cause a slipping hazard. Ventilate area of leak or spill. If available, use foam to smother or suppress. Refer to Section 7, Handling, for additional precautionary measures. See Section 10 for more specific information. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

6.2 Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

6.3 Methods and materials for containment and cleaning up: Contain spilled material if possible. Absorb with materials such as: Dirt. Vermiculite. Sand. Clay. Do NOT use absorbent materials such as: Cement powder (Note: may generate heat). Collect in suitable and properly labeled open containers. Suitable containers include: Metal drums. Plastic drums. Polylined fiber pacs. Wash the spill site with large quantities of water. Attempt to neutralize by adding suitable decontaminant solution: Formulation 1: sodium carbonate 5 - 10%; liquid detergent 0.2 - 2%; water to make up to 100%, OR Formulation 2: concentrated ammonia solution 3 - 8%; liquid detergent 0.2 - 2%; water to make up to 100%. If ammonia is used, use good ventilation to prevent vapor exposure. Contact Dow for clean-up assistance. See Section 13, Disposal Considerations, for additional information.

Section 7. Handling and Storage

7.1 Precautions for safe handling

Handling

General Handling: Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling. Avoid breathing vapor. Use with adequate ventilation. Keep container tightly closed. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Other Precautions: Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Store in a dry place. Protect from atmospheric moisture. Do not store product contaminated with water to prevent potential hazardous reaction. See Section 10 for more specific information. Additional storage and handling information on this product may be obtained by calling your sales or customer service contact.

Storage Period:
6 Months

Storage temperature:
24 - 41 °C

7.3 Specific end uses

See the technical data sheet on this product for further information.

Section 8. Exposure Controls/Personal Protection**8.1 Control parameters Exposure Limits**

Component	List	Type	Value
Aromatic Hydrocarbon	ACGIH	TWA	10 ppm
	ACGIH	STEL	15 ppm
	NIOSH	REL	10 ppm
	NIOSH	STEL	15 ppm
	OSHA Z1	PEL	10 ppm

8.2 Exposure controls**Personal Protection**

Eye/Face Protection: Use chemical goggles. Chemical goggles should be consistent with EN 166 or equivalent.

Skin Protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Hand protection: Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Butyl rubber. Polyethylene. Chlorinated polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Viton. Neoprene.

Polyvinyl chloride ("PVC" or "vinyl"). Nitrile/butadiene rubber ("nitrile" or "NBR"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Respiratory Protection: Atmospheric levels should be maintained below the exposure guideline. When atmospheric levels may exceed the exposure guideline, use an approved air-purifying respirator equipped with an organic vapor sorbent and a particle filter. For situations where the atmospheric levels may exceed the level for which an air-purifying respirator is effective, use a positive-pressure air-supplying respirator (air line or self-contained breathing apparatus). For emergency response or for situations where the atmospheric level is unknown, use an approved positive-pressure self-contained breathing apparatus or positive-pressure air line with auxiliary self-contained air supply.

Use the following CE approved air-purifying respirator: Organic vapor cartridge with a particulate pre-filter, type AP2.

Ingestion: Use good personal hygiene Do not consume or store food in the work area Wash hands before smoking or eating.

Engineering Controls

Ventilation: Use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations. Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines. Exhaust systems should be designed to move the air away from the source of vapor/aerosol generation and people working at this point. The odor and irritancy of this material are inadequate to warn of excessive exposure.

Section 9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance	Liquid.
Physical State	Colorless liquid
Color	Hydrocarbon like
Odor	0.4 ppm <i>based upon literature</i> . Odor is inadequate warning of excessive exposure.
Odor Threshold	NA
pH	NA
Melting Point	NA
Freezing Point	NA
Boiling Point (760 mmHg)	decomposes prior to boiling.
Flash Point - Closed Cup	> 250 °F <i>Literature</i>
Evaporation Rate (Butyl Acetate = 1)	No test data available
Flammability (solid, gas)	Not applicable to liquids
Flammable Limits In Air	Lower: No test data available Upper: No test data available
Vapor Pressure	< 0.00001 mmHg @ 25 °C <i>Literature</i>
Vapor Density (air = 1)	8.5 <i>Literature</i>
Specific Gravity (H ₂ O = 1)	1.05 20 °O/20 °C <i>Literature</i>
Solubility in water (by weight)	insoluble
Partition coefficient, n-octanol/water (log Pow)	No test data available > 230 °C
Autoignition Temperature	<i>Literature</i>
Decomposition Temperature	75 - 150 cPs @ 25 °C <i>ASTM D4889</i>
Dynamic Viscosity	No test data available
Kinematic Viscosity	Not explosive
Explosive properties	No
Oxidizing properties	

9.2 Other information

Molecular Weight	Not applicable
------------------	----------------

Section 10. Stability and Reactivity

10.1 Reactivity

Will react with diisocyanates and the rate of reaction increases with temperature as well as increased contact; these reactions can become violent. Contact is increased by stirring.

The reaction forms carbon dioxide gas and a layer of solid polyurea.

10.2 Chemical stability

Stable under recommended storage conditions. See Storage, Section 7.

10.3 Possibility of hazardous reactions

May occur. Exposure to elevated temperatures can cause product to decompose and generate gas. This can cause pressure build-up and/or rupturing of closed containers. Polymerization can be catalyzed by: diisocyanates

10.4 Conditions to Avoid: Exposure to elevated temperatures can cause product to decompose. Generation of gas during decomposition can cause pressure in closed systems. Pressure build-up can be rapid.

10.5 Incompatible Materials: Avoid contact with: Strong acids. Oxidizers. Diisocyanates. Contact is increased by stirring or if the material mixes with the diisocyanate. The reaction forms carbon dioxide gas and a layer of solid polyurea. Reaction will generate carbon dioxide and heat. The reaction of polyols and isocyanates generate heat.

10.6 Hazardous decomposition products

Decomposition products depend upon temperature, air supply and the presence of other materials. Gases are released during decomposition.

Section 11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity

Ingestion

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury. Typical for this family of materials. LD50, rat > 3,000 mg/kg

Aspiration hazard

Based on physical properties, not likely to be an aspiration hazard.

Dermal

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Typical for this family of materials. LD50, rabbit > 3,000 mg/kg

Inhalation

At room temperature, vapors are minimal due to low volatility. However, certain operations may generate vapor or mist concentrations sufficient to cause respiratory irritation and other adverse effects. Such operations include those in which the material is heated, sprayed or otherwise mechanically dispersed such as drumming, venting or pumping. Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs. May cause pulmonary edema (fluid in the lungs.) Effects may be delayed. Decreased lung function has been associated with overexposure to aromatic hydrocarbons

LC50, 4 h, Aerosol, rat 3,800 mg/m3

Eye damage/eye irritation

May cause moderate eye irritation. May cause slight temporary corneal injury.

Skin corrosion/irritation

Prolonged contact may cause slight skin irritation with local redness May stain skin.

Sensitization

Skin

Skin contact may cause an allergic skin reaction. Animal studies have shown that skin contact with aromatic hydrocarbons may play a role in respiratory sensitization.

Respiratory

May cause allergic respiratory response. Hydrocarbon concentrations below the exposure guidelines may cause allergic respiratory reactions in individuals already sensitized. Asthma-like symptoms may include coughing, difficult breathing and a feeling of tightness in the chest. Occasionally, breathing difficulties may be life threatening.

Repeated Dose Toxicity

Tissue injury in the upper respiratory tract and lungs has been observed in laboratory animals after repeated excessive exposures to Aromatic Hydrocarbon vapors.

Chronic Toxicity and Carcinogenicity

Lung and nasal tumors have been observed in laboratory animals exposed to respirable aerosol droplets of Aromatic hydrocarbons for their lifetime. Tumors occurred concurrently with respiratory irritation and lung injury. Current exposure guidelines are expected to protect against these effects reported for MDI.

Developmental and Reproductive Toxicity

In laboratory animals, fetal effects occurred only at high doses of Aromatic Hydrocarbons which were toxic to the mother.

Section 12. Ecological Information

12.1 Toxicity

The measured ecotoxicity is that of the hydrolyzed product, generally under conditions maximizing production of soluble species. Material is not classified as dangerous to aquatic organisms (LC50/EC50/1C50/LL50/EL50 greater than 100 mg/L in most sensitive species).

Fish Acute & Prolonged Toxicity

No Data Available

Aquatic Invertebrate Acute Toxicity

No Data Available

Aquatic Plant Toxicity

No Data Available

Toxicity to Micro-organisms

No Data Available

Toxicity to Soil Dwelling Organisms

No Data Available

12.2 Persistence and Degradability

No Data Available

12.3 Bioaccumulative potential

Bioaccumulation:

No Data Available

12.4 Mobility in soil

Mobility in soil:

No Data Available

12.5 Results of PBT and vPvB assessment

No Data Available

12.6 Other adverse effects

This substance is not in Annex I of Regulation (EC) No 1005/2009 on substances that deplete the ozone layer.

Section 13. Disposal Considerations

13.1 Waste treatment methods

This product, when being disposed of in its unused and uncontaminated state should be treated as a hazardous waste according to EC Directive 2008/98/EC. Any disposal practices must be in compliance with all national and provincial laws and any municipal or local by-laws governing hazardous waste. For used, contaminated and residual materials additional evaluations may be required. Do not dump into any sewers, on the ground, or into any body of water. Incineration under approved, controlled conditions using incinerators suitable or designed for the disposal of hazardous chemical wastes, is the preferred method for disposal. Empty drums should be decontaminated (see Section 6) and either punctured and scrapped or given to an approved drum reconditioner.

Section 14. Transport Information

ADR/RID**14.1 UN number**

Not applicable

14.2 UN proper shipping name

Proper Shipping Name: NOT REGULATED

14.3 Transport hazard class(es)

Not applicable

14.4 Packing Group

Not applicable

14.5 Environmental hazards

Not considered environmentally hazardous based on available data

14.6 Special precautions for user

Special Provisions: no data available

Hazard identification No: no data available

ADNR/ADN**14.1 UN number**

Not applicable

14.2 UN proper shipping name

Proper Shipping Name: NOT REGULATED

14.3 Transport hazard class(es)

Not applicable

14.4 Packing Group

Not applicable

14.5 Environmental hazards

Not considered environmentally hazardous based on available data

14.6 Special precautions for user

No data available

IMDG

14.1 UN number

Not applicable

14.2 UN proper shipping name

Proper Shipping Name: NOT REGULATED

14.3 Transport hazard class(es)

Not applicable

14.4 Packing Group

Not applicable

14.5 Environmental hazards

Not considered environmentally hazardous based on available data

14.6 Special precautions for user

EMS Number: Not applicable

ICAO/IATA

14.1 UN number

Not applicable

14.2 UN proper shipping name

Proper Shipping Name: NOT REGULATED

14.3 Transport hazard class(es)

Not applicable

14.4 Packing Group

Not applicable

14.5 Environmental hazards

Not considered environmentally hazardous based on available data

14.6 Special precautions for user

no data available

Section 15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

US. Toxic Substances Control Act

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

European Inventory of Existing Commercial Chemical Substances (EINECS)

The components of this product are on the EINECS inventory or are exempt from inventory requirements.

15.2 Chemical Safety Assessment

Not applicable.

Section 16. Other Information

Hazard statement in the composition section

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

Riskphrases in the Composition section

R20	Harmful by inhalation.
R36/37/38	Irritating to eyes, respiratory system and skin.
R40	Limited evidence of a carcinogenic effect.
R42/43	May cause sensitization by inhalation and skin contact.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Product Literature

Additional information on this product may be obtained by calling your sales or customer service contact.

Solid Solution Products urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.